

## LED AREA LIGHTS - (XGBM)



US patent D574994 & 7,828,456 and MX patent 29631 and US & Int'l. patents pending

**SMARTTEC™ THERMAL CONTROL** - LSI drivers feature integral sensor which reduces drive current when ambient temperatures exceed rated temperature.

**OCCUPANCY SENSING (IMS)** - Optional integral passive infrared motion sensor activates switching of luminaire light levels. High level light is activated and increased to full bright in 1-2 seconds upon detection of motion. Low light level (30% maximum drive current) is activated when target zone is absent of motion activity for ~2 minutes and ramps down (10-15 seconds) to low level to allow eyes time to adjust. Sensor is located on the front of optical assembly and rotates with the optic. Sensor optic has a detection cone of approximately 45°. Examples of detection - occurs 30' out from a 30' mounting height pole; occurs 20' out from a 20' mounting height pole.

**ENERGY SAVING CONTROL OPTIONS** - DIM - 0-10 volt dimming enabled with controls by others. BLS - Bi-level switching responds to external line voltage signal from separate 120-277V controller or sensor (by others), with low light level decreased to 30% maximum drive current.

**EXPECTED LIFE** - Minimum 60,000 hours to 100,000 hours depending upon the ambient temperature of the installation location. See LSI web site for specific guidance.

**LEDS** - Select high-brightness LEDs in Cool White (5250°K nominal) or Neutral White (4000°K nominal) color temperature, 70 CRI (nominal).

**DISTRIBUTION/PERFORMANCE** - Types 3, 5, FT and FTA available - field rotatable reflectors.

**HOUSING** - Square, die-formed aluminum. Fully enclosed weather-tight housing contains factory prewired drivers and field connections.

**TOP-ACCESS COVER** - Gasketed, tethered top-access cover provides ease of installation and allows for easy driver access. Four captive stainless-steel fasteners secure the top-access cover to the housing.

**OPTICAL UNIT** - Clear tempered optical grade flat glass lens sealed to aluminum housing creates an IP67 rated, sealed optical unit (includes pressure stabilizing breather). Optical unit can be easily field rotated in 90° increments. Directional arrow on optics allows alignment without the unit being energized.

**MOUNTING** - 2-1/2" x 5-3/8" x 12" extruded aluminum arm mounting bracket shipped standard. Use with 5" traditional drilling pattern. Round Pole Plate (RPP2) required for mounting to 3"-5" round poles. (See Accessory Ordering Information chart.)

**ELECTRICAL** - Two-stage surge protection (including separate surge protection built into electronic driver) meets Location Category C Low. Available with universal voltage power supply 120-277VAC (UE - 50/60Hz input), and 347-480VAC.

**DRIVERS** - Available in Low Watt (LW), Super Saver (SS) and High Output (HO) drive currents (Drive currents are factory programmed). Components are fully encased in potting material for moisture resistance. Driver complies with FCC 47 CFR part 15 RF/EMI standard.

**OPERATING TEMPERATURE** - -40°C to +50°C (-40°F to +122°F).

**FINISH** - Fixtures are finished with LSI's DuraGrip® polyester powder coat finishing process. The DuraGrip finish withstands extreme weather changes without cracking or peeling.

**DECAL STRIPING** - LSI offers optional color-coordinated decals in 9 standard colors to accent the fixture. Decals are guaranteed for five years against peeling, cracking, or fading.

**WARRANTY** - LSI LED fixtures carry a limited 5-year warranty.

**PHOTOMETRICS** - Application layouts are available upon request. Contact LSI Applications Group at [lighting.apps@lsi-industries.com](mailto:lighting.apps@lsi-industries.com)

**SHIPPING WEIGHT (in carton)** - Fixture - 44.5 lbs (20 kg) Arm - 5 lbs. (2kg) arm

**LISTING** -UL listed to U.S. and Canadian safety standards. Suitable for wet locations.

### LIGHT OUTPUT - XGBM

		Lumens (Nominal)				Watts (Nominal)
		Type 3	Type 5	Type FT	Type FTA	
Cool White	LW	14080	13840	15020	16560	140
	SS	20180	18040	20700	23030	187
	HO	26750	25460	29070	31810	300
Neutral White	LW	11450	11290	12220	13470	136
	SS	16390	15170	17230	18750	188
	HO	22240	20550	23510	25410	288

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.

American Innovation



IP67

Fixtures comply with ANSI C136.31-2010 American National Standard for Roadway Lighting Equipment - Luminaire Vibration 3G requirements.

# LED AREA LIGHTS - (XGBM)

## LUMINAIRE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE:	<b>XGBM 5 LED HO CW UE WHT VCM ES</b>
------------------------	---------------------------------------

Prefix	Distribution	Light Source	Drive Current	Color Temperature	Input Voltage	Finish	Optional Controls	Optional Sensor/Options
XGBM <sup>1</sup> - LED Greenbriar	FT - Forward Throw FTA - Forward Throw Automotive 3 - Type III 5 - Type V	LED	LW - Low Watt SS - Super Saver HO - High Output	CW - Cool White NW - Neutral White	UE - Universal Voltage (120-277)  347-480	BLK - Black BRZ - Bronze GPT - Graphite MSV - Metallic Silver PLP - Platinum Plus SVG - Satin Verde Green WHT - White  <b>Optional Color Decals</b> 45 - Light Gold 20 - Charcoal Metallic 55 - Black 94 - Blue Metallic 59 - Dark Green 51 - Dark Red 21 - Tomato Red 50 - White 700 - Aztec Silver Metallic	<b>Virtinet Wireless Network</b> (requires a Ventura controller/Malibu link) (blank) - None VCM - Standard (revenue grade) VCMH - Standard (Host) DIM - 0-10 volt dimming (required for satellite fixtures)  <b>Stand-Alone Control</b> (blank) - None DIM <sup>2</sup> - 0-10V Dimming (from external signal) BLS <sup>3</sup> - Bi-level Switching (from external signal - requires 120-277V controls system voltage)	<b>Sensor</b> ES <sup>4</sup> - External Sensor IMS <sup>5</sup> - Integral Motion Sensor PCI 120 - 120v Button-Type Photocell VCM 208 - 208v Button-Type Photocell PCI 240 - 240v Button-Type Photocell PCI 277 - 277v Button-Type Photocell PCI 347 - 347v Button-Type Photocell  <b>Options</b> 8BK - 8" Bracket (S and D180 only) TB - Terminal Block



LUMINAIRE EPA CHART <sup>2</sup> - XGBM		
	8" Bracket	12" Bracket
Single	2.3	2.4
D180°	4.7	4.8
D90°		4.7
T90°	12" Bracket	7.2
TN120°	Required	7.3
Q90°		8.8

**Note:** House Side Shield adds to fixture EPA. Consult Factory.

ACCESSORY ORDERING INFORMATION (Accessories are field installed)			
Description	Order Number	Description	Order Number
XGBM - HSS - House Side Shield (Black only)	482002 BLK <sup>6</sup>	RPSB120 - Wet Location Remote Box with 120V External Photocell	C/F <sup>7</sup>
RPP2 - Round Pole Plate	162914BLK	RPSB208-277 - Wet Location Remote Box with 208-277V External Photocell	C/F <sup>7</sup>
BKS-BO-WM-* - CLR - Wall Mount Plate	123111CLR	PMOS120 - 120V Pole-Mount Occupancy Sensor	518030CLR <sup>8</sup>
BKA-BO-RA-8-CLR - Radius Arm	169010CLR	PMOS208/240 - 208, 240V Pole-Mount Occupancy Sensor	C/F <sup>8</sup>
BKU-BO-S-19-CLR - Upsweep Bracket for round or square poles	144191CLR	PMOS277 - 277V Pole-Mount Occupancy Sensor	518029CLR <sup>8</sup>
ROSB120 - WL Remote Box with 120V Occupancy Sensor	C/F <sup>7</sup>		
ROSB277 - WL Remote Box with 277V Occupancy Sensor	C/F <sup>7</sup>		

- FOOTNOTES:**
- 1 - Use with 5" traditional drilling pattern
  - 2 - IMS, DIM and BLS are not compatible on SS drive current with 347-480V, consult factory regarding dimming.
  - 3 - IMS, DIM and BLS are not compatible.
  - 4 - Do not specify for satellite units.
  - 5 - Not compatible with Virtinet wireless systems, DIM or BLS.
  - 6 - House Side Shield adds to fixture EPA. HSS must be mounted opposite of IMS. Consult factory.
  - 7 - Includes VCM. To be used in conjunction with VCM option in fixture. Consult factory.
  - 8 - To be used in conjunction with any of the VCM control modules and ES sensor option in fixture. Consult factory.

## DIMENSIONS



**House Side Shield (482002BLK)**

