

LED AREA LIGHTS - AEROMAX™ SMALL (XASU)

US patent 7828456, 7952293, 8002428 and CAN 2693131 & 2701653 and US & Int'l. patents pending



LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens) 7543
Watts 88.4
Lumens per Watt (Efficacy) 86

Color Accuracy
Color Rendering Index (CRI) 74

Light Color
Correlated Color Temperature (CCT) 4899 (Daylight)

Warm White 2700K Bright White 3000K Daylight 4500K 6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: KGGN-NRQ1KL (11/19/2013)
Model Number: XASU 5 LED 64 HO CW UE
Type: Luminaire - Area/Roadway

LIGHT OUTPUT - XASU						
		# of LEDs	Lumens (Nominal)			Watts (nominal)
			Type 3	Type FT	Type 5	
Cool White	SS	64	7000	6200	6100	69
	HO	64	8500	7650	7500	89
Neutral White	SS	64	6700	5700	5600	69
	HO	64	7900	6700	6700	89

This product, or selected versions of this product, meet the standards listed below. Please consult factory for your specific requirements.



Fixtures comply with ANSI C136.31-2010 American National Standard for Roadway Lighting Equipment - Luminaire Vibration 3G requirements.

SMARTTEC™ THERMAL CONTROL - Sensors in both optical unit and driver enclosure reduce drive current when ambient temperatures exceed 50°C. Current is lowered in imperceptible 5% increments every 5 minutes until safe operating temperature is reached.

ENERGY SAVING CONTROL OPTIONS - DIM - 0-10 volt dimming enabled with controls by others. BLS - Bi-level switching responds to a 120-277V signal from separate controller or sensor (by others), with low light level decreased to 30% maximum drive current.

OCCUPANCY SENSOR (IMS) - Optional internal passive infrared motion sensor activates switching of luminaire light levels. High level light is activated and increased to full bright in 1-2 seconds upon detection of motion. Low light level (30% maximum drive current) is activated when target zone is absent of motion activity for ~ 2 minutes and ramps down (10-15 sec.) to low level to allow eyes time to adjust. Sensor is located on the front of optical assembly. Sensor optic has a detection cone of approximately 45°. Examples of detection - occurs 30' out from a 30' mounting height pole; occurs 20' out from a 20' mounting height pole.

EXPECTED LIFE - Minimum 60,000 hours to 100,000 hours depending upon the ambient temperature of the installation location. See LSI web site for specific guidance.

LEDS - Select high-brightness LEDs in Cool White (5000°K nominal) or Neutral White (4000°K nominal) color temperature. 70 CRI (nominal).

DISTRIBUTION/PERFORMANCE - Types 3, FT and 5. Exceptional uniformity creates bright environment at lower light levels. Improved backlight cutoff minimizes light trespass.

HOUSING - One-piece, die-formed aluminum. Weather-tight housing contains factory prewired driver and field connections. Extruded one-piece EPDM gasketed wiring access door (with safety lanyard) is located underneath and utilizes tool-less thumbscrew fastener.

OPTICAL UNIT - Clear tempered optical grade flat glass lens sealed to aluminum optics housing creates an IP67 rated, sealed optical unit (includes pressure-stabilizing breather). Optical unit is recessed into housing cavity and sealed to the housing with extruded one-piece EPDM gasket. Optical unit lanyard serves dual purposes of safety and provides positive ground between unit and housing.

MOUNTING - Tapered rear design allows fixtures to be mounted in a quad pattern without the need for extension arms. Use with 3" reduced drilling pattern on round and square poles. A round pole plate (X4RPP, X5RPP) is required for mounting to round poles. Wall mount available by ordering wall mounting bracket (BKS-XBO-WM-* -CLR). See Accessory Ordering Information chart for all brackets.

ELECTRICAL - A terminal block for attachment of incoming primary wiring is supplied. Two-stage surge protection (including separate surge protection built into electronic driver) meets IEEE C62.41.2-2002, Location Category C. Available with universal voltage power supply 120-277VAC (50/60Hz input), and 347-480 VAC. Optional twistlock photocell receptacle is available. Photocell must be ordered separately.

DRIVER - Available in SS (Super Saver) and HO (High Output) drive currents (Drive currents are factory programmed). Components are fully encased in potting material for IP65 moisture resistance. Driver complies with IEC and FCC standards. Driver and key electronic components can easily be accessed.

OPERATING TEMPERATURE - -40°C to +50°C (-40°F to +122°F).

FINISH - Fixtures are finished with LSI's DuraGrip® polyester powder coat finishing process. The DuraGrip finish withstands extreme weather changes without cracking or peeling.

WARRANTY - LSI LED fixtures carry a limited 5-year warranty.

PHOTOMETRICS - Application layouts are available upon request. Contact LSI Applications Group at lighting.apps@lsi-industries.com

SHIPPING WEIGHT (in carton) - 31 lbs. / 14.1 Kg

LISTING - ETL listed to U.S. and International safety standards. Suitable for wet locations.

LED AREA LIGHTS - AEROMAX™ SMALL (XASU)

LUMINAIRE ORDERING INFORMATION

TYPICAL ORDER EXAMPLE: **XASU FT LED 64 HO CW UE WHT PCR**

Prefix	Distribution	Light Source	# of LEDs	Drive Current	Color Temperature	Input Voltage	Finish	Optional Controls	Optional Sensor/Options
XASU	3 - Type III 5 - Type V FT - Forward Throw	LED	64	SS - Super Saver HO - High Output	CW - Cool White NW - Neutral White	UE - Universal Voltage (120-277) 347-480 - Universal Voltage (347-480V)	BLK - Black BRZ - Bronze GPT - Graphite MSV - Metallic Silver PLP - Platinum Plus SVG - Satin Verde Green WHT - White	Virtinet Wireless Network (requires a Ventura controller/Mailbu link) (blank) - None VCM - Standard (revenue grade) VCMB - Basic VCMH - Standard (Host) VCMBH - Basic (Host) DIM - 0-10 volt dimming (required for satellite fixtures) Stand-Alone Control (blank) - None DIM - 0-10V Dimming (from external signal) ¹ BLS - Bi-level Switching (from external 120-277V signal) ¹	Sensor ES - External Sensor ² IMS - Integral Motion Sensor ³ Options PCR - Photoelectric Control Receptacle ⁴

LUMINAIRE EPA CHART - XASU

	Single	0.9
	D180°	2.0
	D90°	1.6
	T90°	2.7
	TN120°	2.8
	Q90°	3.1

Note: House Side Shield adds to fixture EPA. Consult Factory.

ACCESSORY ORDERING INFORMATION


(Accessories are field installed)

Description	Order Number	Description	Order Number
BKA-XBO-EC-6-CLR 6" Extension Arm	382136CLR	DFK208, 240 Double Fusing (208V, 240V)	DFK208, 240 ⁷
BKS-XBO-WM-* - CLR Wall Mounting Bracket	382132CLR	DFK480 Double Fusing (480V)	DFK480 ⁷
XASU-HSS House Side Shield (Black only)	544103BLK ⁵	FK347 Single Fusing (347V)	FK347 ⁷
X4RPP Round Pole Plate for 4" Poles	379967CLR	ROSB120 - WL Remote Box with 120V Occupancy Sensor	C/F ⁸
X5RPP Round Pole Plate for 5" Poles	379968CLR	ROSB277 - WL Remote Box with 277V Occupancy Sensor	C/F ⁸
PC120 Photocell for use with PCR option (120V)	122514 ⁶	RPSB120 - Wet Location Remote Box with 120V External Photocell	C/F ⁸
PC208-277 Photocell for use with PCR option (208V, 240V, 277V)	122515 ⁶	RPSB208-277 - Wet Location Remote Box with 208-277V External Photocell	C/F ⁸
PC347 Photocell for use with PCR option (347V)	159516 ⁶	PMOS120 - 120V Pole-Mount Occupancy Sensor	518030CLR ⁹
PC480 Photocell for use with PCR option (480V)	1225180 ⁶	PMOS208/240 - 208V, 240V Pole-Mount Occupancy Sensor	C/F ⁸
FK120 Single Fusing (120V)	FK120 ⁷	PMOS277 - 277V Pole-Mount Occupancy Sensor	518029CLR ⁹
FK277 Single Fusing (277V)	FK277 ⁷		


FOOTNOTES:

- 1- IMS, DIM and BLS cannot be ordered together.
- 2 - Do not specify for satellite units.
- 3 - Not compatible with Virtinet wireless systems, DIM or BLS.
- 4 - Photocell must be ordered separately. See Accessories.
- 5 - House Side Shield adds to fixture EPA. Consult factory.
- 6 - Factory installed PCR option required.
- 7 - Fusing must be located in the hand hole of pole.
- 8 - Includes VCM. To be used in conjunction with VCM option in fixture. Consult factory.
- 9 - To be used in conjunction with any of the VCM control modules and ES sensor option in fixture. Consult factory.


DIMENSIONS




Front View



Side View



Bottom View



House Side Shield